

Mobility

- One-handed, thumb-operated user interface
- Highly portable at 1.1 lbs/520 g
- 64 GB of memory, storing over 1000 studies
- Rechargeable swappable battery with one hour of continuous scanning

Clarity

- 7"/17.8 cm 1920 x 1200 pixels high-resolution display
- Image optimization controls
- Measurements and calculation packages for Cardiac and OB
- 2D, M-Mode, Color Doppler and THI, with multiple optimization settings

Connectivity

- Access patient information from EMR and send study to EMR via Synapse® EMR gateway
- Perform and save 12-lead SHL (Smartheart™)* exam along with ultrasound study (not available in all countries)
- Email study images
- Productivity applications such as internet browser, notes etc.
- Access online tutorials through SonoAccess app

Product description

System weight: 1.1 lbs/520 g

Dimensions: 18.3 cm x 11.7 cm x 2.7 cm

 $(L \times W \times H)$

Display: 7"/17.8 cm 1920 x 1200 pixels

high-resolution display

Dual touch screen

Architecture: Android OS, Qualcomm

Snapdragon Chip

Dynamic range: Up to 170 dB Gray scale: 256 shades

EMC Class: B

User interface and controls

- Tablet-like interactive touchscreen interface
- Innovative thumb-operated user interface
- Easily access controls: depth, gain, scale, pan, zoom and steer
- Integrated streamlined protocols (eFAST, FATE, etc.)

Application specific Measurements and Calculations:

OB/GYN/Fertility:

- Measurements: Distance/Ellipse/Trace, GS, CRL, Yolk Sac, BPD, HC, AC, FL, HL, AFI, Cervix Length, Cerebellum
- Calculations: Estimated Fetal Weight,
 Estimated Due Date, Amniotic Fluid Index,
 Average Ultrasound Age

Cardiac:

- Measurements: Distance/Ellipse/Trace/Area, RVWd, RVDd, IVSd, LVDd, LVPWd, RVWs, RVDs, IVSs, LVDs, LVPWs, MVA, AVA
- Calculations: Ejection fraction, Fractional Shortening, Volume, Area
- 12-lead SHL (Smartheart™)

Transducers:

Broadband and Multifrequency:

- Linear, Phased Array

Power supply:

- Rechargeable swappable Lithium-Polymer battery
- 8 hrs standby with 1 hr scanning



Contact 877-299-1786 for detailed specifications.





Transducers

SonoSite designs, manufactures and tests transducers in-house with real-world customer needs in mind. Our transducers exceed stringent specifications for drop testing and splash resistance, so you can use them with confidence in the most demanding of environments.

P21v 5-1 MHz Phased Applications: Abdominal, Cardiology, Lung, OB Scan depth: 32 cm

_38v

10-5 MHz Linear

Applications

Breast, MSK, Superficial,

Nerve, Vascular

Scan depti

9 cm



For detailed information, please speak with your loca SonoSite representative.



FUJIFILM SonoSite, Inc

21919 30th Drive SE, Bothell, Washington 98021-3904 United States
Tel: +1 425 951 1200 Fax: +1 425 951 1201 Email: ultrasound@sonosite.com

www.sonosite.com

Bluetooth is a registered trademark of Bluetooth SIG, Inc. Mac is a trademark of Apple Inc., registered in the U.S. and other countries.

Dicom is the registered trademark of the National Electrical Manufacturers Association for its standards publications relating to digital communications of medical information.

SONOSITE, the SONOSITE logo and IVIZ are trademarks and registered trademarks of FUJIFILM SonoSite, Inc. in various jurisdictions. FUJIFILM is a trademark and registered trademark of FUJIFILM Corporation in various jurisdictions. All other trademarks are the property of their respective owners.